

# Features

Functions	321	322
Compact design	●	●
Auto shut-off	●	●
Display Hold	●	●
Low battery indication	●	●
Current AC	●	●
Volts DC		●

# Specifications

Functions	321		322		321	322
	Range	Resolution	Range	Resolution	Best Accuracy	
Current AC	400.0A	0.1A	40.00A 400.0A	0.01A 0.1A	1.8% ± 5 counts (50 - 60Hz) 3.0% ± 5 counts (60Hz - 400Hz)	1.8% ± 5 counts (50 - 60Hz) 3.0% ± 5 counts (60Hz - 400Hz)
Voltage AC	0-400.0V 400-600V	0.1V 1V	0- 400.0V 400 - 600V	0.1V 1V	1.2% ± 5 counts (50 - 400Hz)	1.2% ± 5 counts (50 - 400Hz)
Voltage DC			0 - 400.0V 400 - 600V	0.1V 1V		1% ± 5 counts
Resistance	0 - 400.0Ω	0.1Ω	0 - 400.0Ω	0.1Ω	1% ± 5 counts	1% ± 5 counts
Continuity	≤ 30Ω		≤ 30Ω			

**Battery Life:** 100 hours typical  
(2 AAA carbon zinc)  
**Size (HxWxD):** 190 mm x 63 mm x 35 mm  
**Jaw Opening:** 25 mm

**Weight:** 0.23 kg  
**Two Year Warranty**

# Combo Kit

**Fluke 117/322 Kit**



# Recommended Accessories



**H3**



**TL223**



**L215**